

Britannia Marine Approved Extinguishers

Our premier range for marine applications in offshore and shipping environments. The Britannia Marine range is acknowledged to be one of the most robust fire extinguishers used by offshore and shipping companies.

These units are externally welded because we know these units are exposed to harsh environmental conditions. We can also supply zinc coated units for additional protection.

The large neck enables the extinguishers to be serviced and refilled quickly in any environment.

Marine and vehicle transport bracket



Britannia Marine Extinguishers							
Extinguisher code	BW9MED	BAF9MED	BT9MED	BC5MED	BA6MED	BA9MED	BA12MED
Propellant type	55gm	75gm	75gm	St'd Pressure	115gm	150gm	150gm
	Gas Cartridge				Gas Cartridge		
Extinguishant	Water	BSX		CO2	ABC Dry powder		
Capacity	9 litres			5kg	6kg	9kg	12kg
Paint primer/ finish	Polyester Red (RAL 3000)			Red (RAL3000)	Polyester Red (RAL 3000)		
Lining	Polymer Lining						
Fire class	A	A,B		B	A,B,C		
Fire rating	21A	21A/183B	21A/183B	70B	27A/183B	34A/233B	43A/233B
Operating temperature	+5 °C to +60 °C			-20 °C to +60 °C			
Test pressure	26 Bar			250 Bar	26 BAR		
Operating pressure @ 20°C	12.5 Bar			50 Bar	12.5 Bar		
Ave. discharge duration	67s	49s	63s	15s	20s	26s	34s
Discharge range	6m	4m	4m	3m	5m	7m	7m
Safe operating distance	2 metres						
Cylinder	Mild Steel			Steel	Mild Steel		
Operating valve	Diecast Zinc Alloy			Brass	Diecast Zinc Alloy		
Height	570mm	570mm	570mm	704mm	525mm	570mm	600mm
Diameter	190mm	190mm	190mm	140mm	165mm	190mm	190mm
Full weight	15.5kg	15.7kg	15.6kg	12.8kg	11.3kg	15.4kg	18.7kg
Empty (excl. cartridge)	5.92kg	5.92kg	6kg	7.3kg	4.5kg	5.43kg	5.65kg
Carton size	195x195x612	195x195x612	195x195x612	210x190x730	179x179x550	195x195x612	195x195x612
Approvals	BS EN3 / Marine Equipment Directive (MED)						