P50 Ecodare F Class Extinguisher

The F Class P50 has been specifically designed to extinguish fat/oil fires. The extinguisher medium forms a seal on the surface preventing re- ignition.

As with all the P50 range the F Class does not require servicing, a simple in-house inspection is all that is required.

Main Approvals Granted

APRAGAZ IBI · MPA Dresden · EN3 · 0029/2017

mca Maritime and Coastguard Agency

Hong Kong Fire Service
Ref No. ECL/FSD/L/50R1/2012

THE P50 RANGE ARE THE ONLY CORROSION FREE, SERVICE FREE, COMPOSITE FIRE EXTINGUISHERS IN THE WORLD

F Class	
Extinguisher code	P50FC
Capacity	6kg
Fire class	F Type
Fire rating	75F
Operating temperature	+5˚c to +60˚c
Test pressure	22bar
Operating pressure @20°C	12bar
Ave. discharge duration	35 Secs
Discharge range	4 metres +
Safe operating distance	1 metre
Cylinder material	HDPE with Aramid winding (Kevlar®)
Operating head material	Brass – C3771 – Nickel Plated
Height	570mm
Diameter	178mm
Full weight	9.08kg
Empty weight	2.26kg
Carton size	198x198x588
Approved to BS EN3	✓